









# PRODUCT KIT GUIDE

2022



# HIKVISION PRODUCT KITS

		Camera		
Type	Model Name	Resolution	Quantity	Form Factor
IP Kit	 <b>EKI-K82T46C</b> ColorVu	4 MP	6	Turret
	 <b>EKI-K41T44</b>	4 MP	4	Turret
	 <b>EKI-K82T46</b> <b>EKI-K82T46B (Black)</b>	4 MP	6	Turret
	 <b>EKI-K164T412</b>	4 MP	12	Turret
	 <b>EKI-K41D44</b>	4 MP	4	Dome
	 <b>EKI-K82D46</b>	4 MP	6	Dome
	 <b>EKI-K164D412</b>	4 MP	12	Dome
	 <b>EKI-K41B44W</b> (Wi-Fi KIT)	4 MP	4	Bullet
Turbo Kit	 <b>EKT-K41T24</b>	2 MP	4	Turret
	 <b>EKT-K82T26</b>	2 MP	6	Turret
	 <b>T7204U1TA4</b>	5 MP	4	Turret
	 <b>T7208U2TA6</b>	5 MP	6	Turret

## Camera

BLC/WDR	IR RANGE	Bracket	Channel	Resolution	HDD
Yes/120 dB	N/A	WMS, PC110T, CBS	8-CH	Up to 8MP	2 TB
Yes/120 dB	30	PC130T,CB130T	4-CH	up to 8MP	1 TB
Yes/120 dB	30	PC130T,CB130T PC130TB, CB130TB	8-CH	up to 8MP	2TB
Yes/120 dB	30	PC130T,CB130T	16-CH	up to 8MP	4 TB
Yes/120 dB	30	PC110,CB110	4-CH	up to 8MP	1 TB
Yes/120 dB	30	PC110,CB110	8-CH	up to 8MP	2 TB
Yes/120 dB	30	PC110,CB110	16-CH	up to 8MP	4 TB
Yes/Digital	30	CBXS	4-CH	up to 4MP	1 TB
Yes/Digital	20	PC110T,CBXS	4-CH	up to 4MP	1 TB
Yes/Digital	20	PC110T,CBXS	8-CH	up to 4MP	2 TB
Yes/Digital	20	PC110T,CBXS	4-CH	up to 5MP	1 TB
Yes/Digital	20	PC110T,CBXS	8-CH	up to 5MP	2 TB

# HIKVISION PRODUCT KITS

## Intercom Kits



### DS-KIS602

DS-KIS602 is an intercom bundle containing 3 products: a modular door station (DS-KD8003-IME1), an indoor station (DS-KH6320-WTE1), and a portable switch that supports Power Over Ethernet (PoE, DS-3E0105P-E/M) to provide powers to the products. A SD Card is included with this bundle.

#### DS-KD8003-IME1 Door Station

- 2 MP HD Video Intercom
- Access Control
- Noise Suppression and Echo Cancellation
- H.264 Video Compression
- Low Illumination
- Tamper Alarm
- Fisheye Camera with Supplemental IR Light
- Supports Sub-Module Access (Maximum of 8)
- Easy-To-Add Additional Modules
- PoE, Standard

#### DS-KH6320-WTE1 Indoor Station

- New UI v2.0: User-Friendly Design
- 7" Colorful IPS Capacitive Touch Screen with 1024 x 600 Resolution
- Standard PoE
- Stores Messages and Captured Pictures on SD Card
- Remote Unlocking via Client Software or Mobile Client
- Views Live Videos of Door Stations and External Cameras
- Supports Wireless Network

Note: The DS-3E0105P-E/M PoE Switch connects the video door station to the video intercom indoor station. It contains four PoE connection ports.



### DS-KIS702-P

DS-KIS702-P provides outstanding image quality, convenient mobile control anytime, anywhere. Excellent touch experience, plug & play and easy installation. Includes one Two-Wire Door Station (DS-KD8003-IME2), one Two-Wire Indoor Station (DS-KH6320-WTE2), a Two-Wire Power & Data Distributor (DS-KAD704), and a door station accessory package (DS-KD-ACW1)

#### DS-KD8003-IME2 2-wire Door Station

- 2 MP HD Video Intercom
- Access Control
- Noise Suppression and Echo Cancellation
- H.264 Video Compression
- Low Illumination
- Tamper Alarm
- Fisheye Camera with Supplemental IR Light
- Supports Sub-Module Access (Maximum of 8)
- Easy-To-Add Additional Modules

#### DS-KH6320-WTE2 Indoor Station

- New UI v2.0: User-Friendly Design
- 7" IPS Capacitive Color Touch Screen with 1024 x 600 Resolution
- Two-Pin Wire for Power Supply and Network Access
- Stores Messages and Captured Pictures on MicroSD Card
- Remote Unlocking via Client Software or Mobile Client
- Views Live Videos of Door Stations and External Cameras
- Supports Wireless Network

#### DS-KAD704 Distributor

- 4 Connection Ports (Ports 1-4)
- 4 Network Status Display Indicators

#### DS-KD-ACW1

##### Door Station Accessory Package

- Installation Frame, Cover, Screws, etc.
- Aviation Aluminum

## Access Control Kits

Available  
Spring 2022



### **DS-K2602-KIT and DS-K2604-KIT (Shown)**

#### **DS-K2602/2604-G Access Controller:**

- 32-bit High-speed Processor
- Encrypted Communication Data
- RS-485 and Wiegand Card Reader Interface
- UL294
- Zone Alarm Input
- Anti-Passback, Multi-Card, First Card, Super Card and Super Password functions
- 32-video channels and 4-door

#### **DS-K1107AMK Card Reader:**

- 32-bit high-speed Processor
- RS-485 and Wiegand Protocol, OSDP protocol
- Tampering Alarm
- Keypad
- Built-in Buzzer to Identify the Reading Status
- 2 x DS-K1107AMK in DS-K2602-KIT, or 4 x DS-K1107AMK in DS-K2604-KIT

#### **IC S50 Mifare Card:**

- Mifare 1 Non-contacting IC Card x 25
- ISO/IEC 14443A Standard

#### **HikCentral Professional License**

- 32-video channels and 4-door



### Contact Information

Toll-Free: +1-855-655-9888

Technical Support: [techsupport.ca@hikvision.com](mailto:techsupport.ca@hikvision.com)

Connect with us:      | [www.hikvision.ca](http://www.hikvision.ca)

Disclaimer: This User Guide is for general information about Hikvision's NVR configuration system ("System") only. Hikvision's warranty of the System shall be subject to Hikvision RMA policy available at <https://ca.hikvision.com/en/support-resources/warranty-rma/rma-policy-ca> where credit warranty will be voided for products with modification or alteration.

©2022 Hikvision USA Inc. and Hikvision Canada Inc. All rights reserved. Hikvision is a registered trademark of Hikvision Digital Technology Co., Ltd. in the US, Canada and other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Product specifications and availability are subject to change without notice.