

DS-2CE56H5T-VPIT3ZE

5 MP Outdoor Ultra-Low Light Varifocal PoC Dome Camera



- 5 MP High Performance CMOS
- Analog HD Output, up to 2560 x 1944 Resolution
- Ultra-Low Light
- 2.8 mm to 12 mm Motorized Varifocal Lens
- OSD Menu, DNR, DWDR
- EXIR 2.0 with up to 130 ft (40 m) IR Range
- PoC.at
- Up-the-Coax (HIKVISION-C)
- IP67, IK10 Protection

The Hikvision DS-2CE56H5T-VPIT3ZE 5 MP Outdoor Ultra-Low Light Varifocal Power-over-Coax (PoC) Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters).

The 2.8 mm to 12 mm lens is optimized for viewing angles that fit any situation. DWDR (Digital Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.







Available models:
DS-2CE56H5T-VPIT3ZE



Specifications

DS-2CE56H5T-VPIT3ZE	
Camera	
Image Sensor	5 MP progressive scan CMOS
Resolution	2560 (H) × 1944 (V)
Minimum Illumination	Color: 0.008 lux @ (f/1.2, AGC on), 0 lux with IR
Shutter Speed	PAL: 1/25 s to 1/50,000s; NTSC: 1/30 s to 1/50,000s
Lens	2.8 mm to 12 mm motorized vari-focal lens
Horizontal Field of View	102° to 31°
Lens Mount	Ø14
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°; tilt: 0° to 75°; rotate: 0° to 355°
Synchronization	Internal synchronization
Frame Rate	2560 × 1944 @ 20 fps, 2560 × 1944 @ 12.5 fps; 2560 × 1440 @ 30 fps, 2560 × 1440 @ 25 fps (default); 1920 × 1080 @ 30 fps, 1920 × 1080 @ 25 fps <i>*2560 × 1944 @ 12.5 fps is not available in PoC mode.</i>
Menu	
AGC	Supported
D/N Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Supported
DWDR (Digital Wide Dynamic Range)	Supported
Language	English
Functions	Brightness, sharpness, DNR, mirror, Smart IR
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%/PoC.at
Power Consumption	Maximum 8 W
Ingress Protection	IP67, IK10
Material	Metal
IR Range	Up to 130 ft (40 m)
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	Ø 5.72" × 4.89" (Ø 145.2 mm × 124.1 mm)
Weight	Approximately 3.53 lbs (1.6 kg)

Accessories

					
CPM + PC140 Ceiling Pendant Mount and 140 mm Pendant Cap	WML+ PC140 Wall Mount Long and 140 mm Pendant Cap	PM Pole Mount Adaptor	RCM-2 Recessed Ceiling Mount	AB135 Inclined Ceiling Mounting Bracket	CM Corner Mount Adapter

Dimensions

